

AMENDMENTS TO THE CLAIMS

The claims in this listing will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) Method for producing a fiber-composite material for producing fiber-composite components, the fiber-composite material comprising reinforcement fibers, resin and a filler, ~~characterized in that the filler comprises~~ comprising at least one of ground and/or and cut reinforcement fibers.
2. (Currently Amended) Method according to claim 1, ~~characterized in that the~~ wherein the filler comprises ground fibers having a particle size of the ground filler is less than 2 mm.
3. (Currently Amended) Method according to claim 1, ~~characterized in that the~~ wherein the filler comprises cut fibers having a size of the cut fibers is less than 20 mm.
4. (Currently Amended) Method according to claim 1, ~~characterized in that~~ wherein the at least one of ground material and/or the and cut reinforcement fibers is mixed with the resin that forms the a subsequent matrix of the fiber-composite component.
5. (Currently Amended) Method according to claim ~~[[1]] 4, characterized in that~~ wherein the resin filler mixture is processed into a film.
6. (Currently Amended) Method according to claim 5, ~~characterized in that~~ wherein the resin filler film is applied to a semi-finished textile product products, e.g., woven fabrics, braided fabrics, knitted fabrics, unidirectional or multiaxial laid fabrics.
7. (Currently Amended) Method according to claim ~~[[1]] 6, characterized in that~~ wherein the resin filler film is introduced as such into a component mold before the actual semi-finished textile product is placed in the component mold, e.g., as a preform.

8. (Currently Amended) Method according to claim 1, ~~characterized in that~~
wherein the resin-filler mixture fiber-composite material is applied into a component
mold or onto a semi-finished textile product in a spray method.

9. (Currently Amended) Method according to claim [[1]] ~~8~~, ~~characterized in that~~
wherein the semi-finished textile products product sprayed with the resin filler mixture
are material is also used for producing preforms.

10. (Canceled)

11. (New) Method according to claim 6, wherein the semi-finished textile
product comprises woven fabrics, braided fabrics, knitted fabrics, unidirectional fabrics
or multiaxial laid fabrics.

12. (New) Method according to claim 7, wherein the resin filler film comprises a
preform.